

NOTES:

ELECTRICAL:

1. CONTACT RESISTANCE : 20M OHMS MAX
2. INSULATION RESISTANCE : 500M OHMS MIN @ 500V DC
3. WITHSTAND VOLTAGE : DC1000V AC700V RMS 60Hz, 1MIN
4. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

1. STORAGE : -40° TO+70°
2. OPERATION : -10° TO+60°

MECHANICAL

1. SHIELD MATERIAL:copper with nickel plated
2. PC UL94V0 TERMINAL:PHOSPHOR BRONZE, TIN PLATING
3. RJ45 CONTACT LIFE: 750 TIMES MIN
4. IDN LIFE : 250 TIMES MIN
5. RJ45 DIMENSION:11.9MM\*9.8MM

TYPE

1. SHIELDED CAT.6 inline coupler
2. COLOUR:SILVERY WHITE


RoHS COMPLIANT

PACKING: 1pcs/PE bag+labl<sub>100</sub> pcs/box+labl<sub>800</sub> pcs/carton

MATERIAL LIST:

③	MODULAR COVER	FIREPROOF PC UL94V0	1	
②	RJ 45 JACK INSERT	8P8C 3U" GOLD PLATED	8	
①	PCB	1.6mm UL 94V0	1	

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
		NEW	2017-11-1	A
BY	CHK		DATE	REV.

 <b>Shenzhen Copperled Technology Co.,Ltd</b>			
TITLE:FTP Cat.6A Inline Coupler		P/N:CL-KJ-C6A07	
CUSTOMER		ITEM NO.	
PRODUCT NAME		UNO ITEM NO.	UNIT
DRAWNBY	CHECKBY	APPOBY	DATE