



COVER

- Material:
- 1.RJ45 Housing:PC
 - 2.Phosphor Bronze with 50-60 micro-inch Nickel plated.
 - 3.Contact area: 3-50 micro-inch Gold plated
 - 4.IDC Housing: PC
 - 5.IDC Terminal material & finished:
 - 5-1.Phosphor Bronze with 50 micro-inch Tin-Lead plated. Over 50-60 micro-inch Nickel plated.
 - 5-2.Use for 22-26 AWG stranded and solid wire
 - 6.Jack Bracket Set:ABS Black color
 - 7.PCB: FR4 UL 94V0

- Performance:
- a.The IDC color combine two wirings of T568A & T568B.
 - b.Insertion Force: 900 grms for 8 contacts
 - c.Retention Strength: 7.7kgs between Jack and Plug
 - d. Operation Temperature: -40°C to 70°C.
 - e.Durability:
 - e-1.Jack:750 cycles Plug-Jack mating and unmating test.
 - e-2. IDC: Max 200 punching times.

| TITLE: | | |  Shenzhen Copperled Technology Co.,Ltd | |
|----------|-------|------------|---|--|
| | INCH | MM | | |
| .X | .015 | .30 | TITLE: UTP Cat.6A Keystone Jack 180 Degree | |
| .XX | .010 | .10 | | |
| .XXX | .005 | .05 | | |
| DRAWN BY | MA | | P/N: CL-KJ-C6A20 | |
| CHECK BY | SCALE | 1:1 |  REV | |
| | UNIT | MM | | |
| APPD BY | SHEET | 1/1 | DWG NO: | |
| | DATE | 2018/03/21 | | |